

Vertical Mount Side Lights

LED 2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Bronze or Polymer
 Finish: Chrome Plated, White Epoxy Coated or Black
 Dimensions: Length: 3-1/4", Width: 2", Projection: 1-1/4"
 Screw Size: #8
 Voltage: 12V or 24V LED
 Wattage: 1.2 watts 2.4 watts (each light)
 Amperage: 0.1 amps 0.1 amps (each light)
 Features: Low Heat & Long Life



Fig. 0602
Chrome



Black



White



Finish	Voltage	Retail Pkg.*	OEM Bulk Pkg.*
Chrome	12	0602DP1CHR	0602001CHR
Black	12	0602DP1BLK	0602001BLK
White	12	0602DP1WHT	0602001WHT
Chrome	24	0602DP2CHR	0602002CHR
Black	24	0602DP2BLK	0602002BLK
White	24	0602DP2WHT	0602002WHT

*Sold in pairs.

LED 1-mile (USCG 1nm) Certified - Patent #D665,1135

Use on Power Driven Vessels Under 12m (39.4.) in Length

Material: Stainless Steel
 Finish: Polished, Black, or White Powder Coated
 Dimensions: Length: 2-1/2", Width: 2-5/8", Projection: 5/8"
 Screw Size: #8
 Voltage: 12V LED
 Wattage: 2.6 watts (each light)
 Amperage: 0.2 amps (each light)
 Features: Ultra Low Profile, Low Heat & Long Life



STEALTH Series
Fig. 0617 Polished



White



Black



Finish	Retail Pkg.*	OEM Bulk Pkg.*
Polished SS	0617DP2STS	0617000STS
Black	0617DP2BLK	0617000BLK
White	0617DP2WHT	0617000WHT

*Sold in pairs.

Spare gasket kit required for mounting on metallic surfaces (optional for fiberglass surfaces and included in DP package): 0617000GKT

Spare Parts Information

L.E.D.'s have no user serviceable parts