

Stern Lights

2-mile (USCG 2nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	Brass or Stainless Steel with Polymer Base
Finish:	Chrome Plated or Polished
Dimensions:	O.D.: 3", Depth: 1"
Screw Size:	#8
Voltage:	12V (Bulb Included)
Wattage:	10 watts
Amperage:	.74 amps
Features:	Flush Mount

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0946DP112V	094600112V
Polished SS	0946DP1STS	0946001STS



Fig. 0946
Vertical Mt. Stern



Coordinating cockpit lights available: See Fig. 1146 on page 64.

2-mile (USCG 2nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	Brass or Stainless Steel Top, Black Base
Finish:	Chrome Plated or Polished
Dimensions:	Height: 3-3/8", Width: 5-3/16", Depth: 1-1/2"
Screw Size:	#8
Voltage:	12V (Bulb Included)
Wattage:	10 watts
Amperage:	.74 amps
Features:	Flush Mount

Finish	Retail Pkg.
Chrome	0939DP112V
Polished SS	0939DP1STS



Fig. 0939
Vertical Mt. Stern



2-mile (USCG 2nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	Brass or Stainless Steel Top and Polymer Base
Finish:	Chrome Plated or Polished
Dimensions:	O.D. Base: 2-3/8", Height: 1-5/8"
Screw Size:	#4
Contacts:	Gold Plated
Voltage:	12V (Bulb Included)
Wattage:	10 watts
Amperage:	.80 amps

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0965DP0CHR	0965000CHR
Polished SS	0965DP0STS	0965000STS



Fig. 0965
Horizontal Mt. Stern



Fig. 0965 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulb provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24 volt applications on new construction.

Spare Parts Information

Fig. 0946:

Bulbs: 0070DP0CLR.
Socket Assembly: 0946DP199B.
Lens with O-Ring: 0946DP099A.
Mounting Flange: 094600099C.



Fig. 0070

Fig. 0939:

Bulbs: 0070DP0CLR.
Socket Assy: 0939DP199A.
Lens with O-Ring: 0284DP0CLR.
Mount w/Flange: 093900099C



Fig. 0284

Fig. 0965:

Lens (Open Top): 0281DPAWHT.
Lens(Closed Top): 0295DPOWHT.
Bulbs: 0071DP0CLR.
Base with Socket Assembly: 0135.



Fig. 0071



Fig. 0295



Fig. 0281