



White All-Round Navigation Lights

0201 Head Style

Alpha Series

2-mile (USCG 2nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

White Translucent Polymer Globe with Polymer Top and Material:

3/4" Anodized Aluminum Tube

Fig. 1138: Chrome Plated Zinc Alloy Base

Chrome and Black Finish: Contacts: **Gold Plated**

Screw Size:

Voltage: 12V (Bulb Included)

12 or 24V (0170SWB Only)

24V Wattage: 11 watts 15 watts Amperage: .94 amps .63 amps

Features:

Fig. 0170: **Fixed Mount** - two pole lengths, two voltages

Fig. 1301: Fixed Mount - one pole length size

Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less

than 18" long, include adapters available for flat

or "V" type 45° mounts and a notch for through base wiring.

Fig. 1134: **Horizontal Mount** - Folds down 90° in either direction

opposite the plane of attachment plate of the mount.

Fig. 1137: **Vertical Mount** - Folds down 90° in either direction along

the plane of attachment plate of the mount.

Fig. 1138: **Quick Adjust Lever** - Ideal for use on pontoon boat square

rails or any flat mounting surface.

Fixed & Folding Mount Options



Fig. 1134 Horizontal Mount



Fig. 1137 Vertical Mount



Fig. 1138 Quick **Adjust Handle**



Figs. 0170SWB and 1301 **Fixed Mount**

Base Mount Fixed Mt. Fixed Mt.	Voltage 12 24	Height Overall 5-1/8" 5-1/8"	Base Dimensions 1" x 2-5/8" 1" x 2-5/8"	Retail Pkg. 0170SWBDP1 0170SWBDP2	OEM Bulk Pkg. 0170SWB12V 0170SWB24V
Fixed Mt.	12	8-1/2"	1" x 2-5/8"	1301DP0CHR	1301000CHR
Folding					
Horizontal Mt.	12	15-5/8"	2"x 1-1/2"	1134DP0CHR	1134000CHR
Vertical Mt.	12	15-1/2"	2-1/4" x 5/8"	1137DP0CHR	1137000CHR
Quick Adjust Mt.	12	15-3/8"	2-1/4" x 5/8"	1138DP0CHR*	1138000CHR*

^{*} Refers to Prop 65 Warning



Fig. 0337

Spare Parts Information

24 Volt Bulb For Fig. 0170SWB: 0337014DP. Globe: 0201DP0WHT.

Replacement bases for Figs. 1134, 1137 & 1138 see page 41



Fig. 0201

PROP 65

(Contains Lead)

Fig. 1137 Vertical Mt. (Shown)

